Final Agenda February 23, 2021



BOROUGH COUNCIL REGULAR MEETING AGENDA FEBRUARY 23, 2021 AT 7:00 P.M.

CALL TO ORDER

This meeting is being held in compliance with the Open Public Meeting Law in that the requirements of the law have been met with the posting of the meeting notice on the Municipal Bulletin Board, filed with the Borough Clerk and forwarded to The Courier News and The Star Ledger.

PLEDGE OF ALLEGIANCE

OPENING PRAYER

ROLL CALL

Mayor Robert Fazen Council President Abel Gomez

- C. Jake Hardin
- C. Richard Jannuzzi
- C. Brad Galeta
- C. Vinnie Petti
- C. Anthony Pranzatelli

APPROVAL OF MINUTES

| February 9, 2021-Regular Meeting | | | | | |
|----------------------------------|-----------------|------------------------|--|--|--|
| Motion: Secon | d: | | | | |
| Roll Call: | | | | | |
| C. Abel Gomez | C. Jake Hardin | C. Richard Jannuzzi | | | |
| C. Brad Galeta | C. Vinnie Petti | C. Anthony Pranzatelli | | | |



February 9, 2021- Executive Session

| Motion: Secon | nd: | |
|----------------|-----------------|------------------------|
| Roll Call: | | |
| C. Abel Gomez | C. Jake Hardin | C. Richard Jannuzzi |
| C. Brad Galeta | C. Vinnie Petti | C. Anthony Pranzatelli |

ADVERTISED HEARING OR SPECIAL PRESENTATION

COVID-19 UPDATE

MAYORAL APPOINTMENT

2021 Somerset County Community Block Grant Committee

Hector Herrera Dale Leubner

PRESENTATION OF COMMUNICATIONS, PETITIONS, ETC.

GREETINGS FOR COMMENTS AND INVITATIONS FOR DISCUSSION

OPENING OF BIDS

ENGINEER'S REPORT- DALE LEUBNER, SUPERINTENDENT OF PUBLIC WORKS

COMMITTEE REPORTS

Chair of Finance – C. Anthony Pranzatelli

Liaison Committees: Architectural Review Advisory Committee, Bound Brook Seniors

Chair of Public Works, Bldgs., Grounds & Utilities – C. Vinnie Petti Liaison Committees:

Chair of Public Safety (Police & Fire) – Council President Abel Gomez Liaison Committees: Board of Engineers, Board of Education, Historic Preservation Commission, Office of Emergency Management, Rescue Squad, Parking Commission,



Chair of Personnel, Administration & Ordinances - C. Brad Galeta Liaison Committees: BB/SBB Municipal Alliance/Youth Services Commission, Recreation Commission, Shade Tree Commission

Chair of Economic Development C. Jake Hardin

Liaison Committees: Planning Board, Special Improvement District

Chair of Zoning, Construction & Code Enforcement - C. Richard Jannuzzi

| Liaison Committees: | Board of Health, Library Advisory Committee | | | |
|---------------------|--|--|--|--|
| INTRODUCTION (| OF ORDINANCES – FIRST READING | | | |
| Ordinance 2021-04 | An Ordinance of the Borough of Bound Brook Authorizing the Execution of a Lease Agreement between the Borough of Bound Brook and Bound Brook Hose Company No. 1 Inc., for Use of a Designated Portion of the Premises Located at 510 East Main Street, Bound Brook, New Jersey | | | |
| | Motion: Movant: I move the ordinance be passed on first reading, advertised according to law and a public hearing be held on March 9, 2021. | | | |
| | Second: | | | |
| | Roll Call: | | | |
| | C. Abel Gomez C. Jake Hardin C. Richard Jannuzzi C. Brad Galeta C. Vinnie Petti_ C. Anthony Pranzatelli | | | |
| Ordinance 2021-05 | An Ordinance of the Borough of Bound Brook Authorizing the Execution of a Lease Agreement between the Borough of Bound Brook and Relief Fire Company No. 4 Inc. for Use of a Designated Portion of the Premises Located at 17 Van Keuren Avenue, Bound Brook, New Jersey | | | |
| | Motion: Movant: I move the ordinance be passed on first reading, advertised according to law and a public hearing be held on March 9, 2021. | | | |
| | Second: | | | |
| | Roll Call: | | | |
| | C. Abel Gomez C. Jake Hardin C. Richard Jannuzzi C. Brad Galeta C. Vinnie Petti C. Anthony Pranzatelli | | | |



| Ordinance 2021-06 | Ordinance Appropriating \$150,000.00 from the Capital Fund Balance for the Cost Associated with the Design of the Hamilton Street Plaza in and by the Borough of Bound Brook, in the County of Somerset, New Jersey | | | |
|-------------------|---|--|--|--|
| | Motion: Movant: I move the ordinance be passed on first reading, advertised according to law and a public hearing be held on March 9, 2021. | | | |
| | Second: | | | |
| | Roll Call: | | | |
| | C. Abel Gomez C. Jake Hardin C. Richard Jannuzzi C. Brad Galeta C. Vinnie Petti_ C. Anthony Pranzatelli | | | |
| ORDINANCE ON 1 | FINAL READING AND CONSIDERATION- SECOND READING | | | |
| Ordinance 2021-03 | AN ORDINANCE AMENDING AND SUPPLEMENTING CHAPTER 21, "LAND USE", SECTION 15, "STORMWATER CONTROL", OF THE REVISED GENERAL ORDINANCES OF THE BOROUGH OF BOUND BROOK | | | |
| | Motion to open public comment: Second: Public Comment: Motion to close public comment: Second: | | | |
| | Motion: Movant: I move the ordinance be passed on second reading and advertised according to law. | | | |
| | Second: Discussion: | | | |
| | Roll Call: | | | |
| | C. Abel Gomez C. Jake Hardin C. Richard Jannuzzi C. Brad Galeta C. Vinnie Petti_ C. Anthony Pranzatelli_ | | | |



INTRODUCTION/DISCUSSION OF RESOLUTIONS

The resolutions listed below were submitted to the Governing Body for review and will be adopted by one motion.

If separate discussion is desired, the resolution may be removed by council action.

| Motion: | Second: | Discussion: | All in Favor: | | |
|----------|---|------------------------|---|--|--|
| 2021-035 | Resolution Authorizing 2020 |) Budget Transfers | | | |
| 2021-036 | Resolution Requesting that Somerset County, the State of New Jersey, and the Congress and Executive Branches of the United States Provide Covid-19 Related Financial Support to Nonprofit Veteran and Community Service Organizations | | | | |
| 2021-037 | Resolution Authorizing an Agreement with Middlesex County for the Use of a Shared Radio Network | | | | |
| 2021-038 | 9 | • • | onduct Professional Surveying and Authorizing a Payment Not | | |
| 2021-039 | | 11887-2018, 011129-2 | ments Pursuant to New Jersey 2019 and 012268-2020 for 423- nt of \$4,321.25 | | |
| 2021-040 | Notification of Applications Development Block Grant by within the Borough of Bound | y the following Nonpro | • | | |

UNFINISHED BUSINESS

NEW BUSINESS



APPROVAL OF VOUCHERS

| Resolution Approving Vouchers in the Amount of \$2,673,39 |) 6.4 | 44 |
|---|--------------|----|
|---|--------------|----|

Motion: Second:

Roll Call:

C. Abel Gomez___ C. Jake Hardin__ C. Richard Jannuzzi__ C. Brad Galeta___ C. Vinnie Petti__ C. Anthony Pranzatelli__

OPEN TO THE PUBLIC FOR COMMENT

AUTHORIZE EXECUTIVE SESSION

2021-042 Resolution Authorizing Executive Session

Motion: Second: All in favor:

ADJOURNMENT

Motion: Second: All in favor:

BOROUGH OF BOUND BROOK County of Somerset

ORDINANCE NO. 2021-04

AN ORDINANCE OF THE BOROUGH OF BOUND BROOK AUTHORIZING THE EXECUTION OF A LEASE AGREEMENT BETWEEN THE BOROUGH OF BOUND BROOK AND BOUND BROOK HOSE COMPANY NO. 1 INC., FOR USE OF A DESIGNATED PORTION OF THE PREMISES LOCATED AT 510 EAST MAIN STREET, BOUND BROOK, NEW JERSEY

WHEREAS, Bound Brook Hose Company 1 INC. ("Company No. 1) owns real property known as 510 E Main Street, Bound Brook, New Jersey and designated on the official tax map of the Borough of Bound Brook as Block 1, Lot 67; and

WHEREAS, the Borough of Bound Brook ("Borough") wishes to enter into a written lease agreement with Company No. 1 for a portion of the real property located at 510 E Main Street, Bound Brook, in the Borough of Bound Brook and identified as Block 1, Lot 67 of the Tax Assessment Map of the Borough of Bound Brook; and

WHEREAS, Company No. 1 has represented to the Borough that it is a non-profit corporation organized as a social welfare organization within the meaning of Section 501(c)(4) of the Internal Revenue Code, as amended, and specifically for the purposes of rendering fire services; and

WHEREAS, N.J.S.A. 40A-12-1 et. seq. authorizes a municipality to lease property in certain circumstances, including for a public benefit or use; and

WHEREAS, the Borough finds such lease to be in the best interest of the residents of the Borough of Bound Brook in order to support and ensure firefighting and related services are provided to the Borough residents; and

WHEREAS, the Governing Body has reviewed the Lease Agreement and wishes to authorize the Mayor to execute same on behalf of the Mayor and Council.

NOW, THEREFORE, BE IT ORDAINED AND ENACTED by the Borough Council of the Borough of Bound Brook that it hereby authorizes and approves the Mayor to execute and the Borough Clerk to attest, a lease agreement between the Borough of Bound Brook and Bound Brook Hose Company 1 INC for a one-year term, in the form attached hereto; and

IT IS FURTHER ORDAINED THAT, if any part of this Ordinance is for any reason held to be invalid, such decision shall not affect the validity of the remaining portion of the ordinance; and

| IT IS FURTHER ORDAINED approval and publication, as required by | | nance shall | take effect | upon | passage |
|---|------|-------------|-------------|------|---------|
| | D.v. | | | | |
| Jasmine D. Mathis | By: | Mayor Rob | ert Fazen | | |
| Borough Clerk | | | | | |
| Date of Introduction: February 23, 202 | 1 | | | | |

BOROUGH OF BOUND BROOK County of Somerset

ORDINANCE NO. 2021-05

AN ORDINANCE OF THE BOROUGH OF BOUND BROOK AUTHORIZING THE EXECUTION OF A LEASE AGREEMENT BETWEEN THE BOROUGH OF BOUND BROOK AND RELIEF FIRE COMPANY NO. 4 INC FOR USE OF A DESIGNATED PORTION OF THE PREMISES LOCATED AT 17 VAN KEUREN AVENUE., BOUND BROOK, NEW JERSEY

WHEREAS, Relief Fire Company No. 4 INC ("Company No. 4) owns real property known as 17 Van Keuren Ave., Bound Brook, New Jersey and designated on the official tax map of the Borough of Bound Brook as Block 21, Lot 13; and

WHEREAS, the Borough of Bound Brook ("Borough") wishes to enter into a written lease agreement with Company No. 4 for a portion of the real property located at 17 Van Keuren Ave, in the Borough of Bound Brook and identified as Block 21, Lot 13 of the Tax Assessment Map of the Borough of Bound Brook; and

WHEREAS, Company No. 4 has represented to the Borough that it is a non-profit corporation organized as a social welfare organization within the meaning of Section 501(c)(4) of the Internal Revenue Code, as amended, and specifically for the purposes of rendering fire services; and

WHEREAS, N.J.S.A. 40A-12-1 et. seq. authorizes a municipality to lease property in certain circumstances, including for a public benefit or use; and

WHEREAS, the Borough finds such lease to be in the best interest of the residents of the Borough of Bound Brook in order to support and ensure firefighting and related services are provided to the Borough residents; and

WHEREAS, the Governing Body has reviewed the Lease Agreement and wishes to authorize the Mayor to execute same on behalf of the Mayor and Council.

NOW, THEREFORE, BE IT ORDAINED AND ENACTED by the Borough Council of the Borough of Bound Brook that it hereby authorizes and approves the Mayor to execute and the Borough Clerk to attest, a lease agreement between the Borough of Bound Brook and Relief Fire Company No. 4 INC for a one-year term, in the form attached hereto; and

IT IS FURTHER ORDAINED THAT, if any part of this Ordinance is for any reason held to be invalid, such decision shall not affect the validity of the remaining portion of the ordinance; and

IT IS FURTHER ORDAINED THAT, the Ordinance shall take effect upon passage, approval and publication, as required by law.

| ATTEST: | APPROVED: | |
|------------------------------------|--------------------|--|
| | By: | |
| Jasmine D. Mathis Borough Clerk | Mayor Robert Fazen | |

Date of Introduction: February 23, 2021

BOROUGH OF BOUND BROOK County of Somerset

ORDINANCE NO. 2021-06

ORDINANCE APPROPRIATING \$150,000.00 FROM THE CAPITAL FUND BALANCE FOR THE COST ASSOCIATED WITH THE DESIGN OF THE HAMILTON STREET PLAZA IN AND BY THE BOROUGH OF BOUND BROOK, IN THE COUNTY OF SOMERSET, NEW JERSEY

NOW THEREFORE, BE IT ORDAINED BY THE BOROUGH COUNCIL OF THE BOROUGH OF BOUND BROOK, IN THE COUNTY OF SOMERSET, NEW JERSEY AS FOLLOWS:

Section 1. \$150,000.00 is hereby appropriated from the Capital Fund Balance of the Borough of Bound Brook, in the County of Somerset, New Jersey (the "Borough") for the design of the Hamilton Street Plaza, and further including all related costs and expenditures incidental thereto.

Section 2. The Borough hereby certifies that it has adopted a capital budget or a temporary capital budget, as applicable. The capital or temporary capital budget of the Borough is hereby amended to conform with the provisions of this ordinance to the extent of any inconsistency herewith. To the extent that the purposes authorized herein are inconsistent with the adopted capital or temporary capital budget, a revised capital or temporary capital budget has been filed with the Division of Local Government Services.

Section 3. This ordinance shall take effect after final adoption and publication and otherwise as provided by law.

By:

Mayor Robert Fazen

Jasmine D. Mathis, Borough Clerk

Attest:_

BOROUGH OF BOUND BROOK County of Somerset

ORDINANCE NO. 2021-03

AN ORDINANCE AMENDING AND SUPPLEMENTING CHAPTER 21, LAND USE, SECTION 15, STORMWATER CONTROL, OF THE REVISED GENERAL ORDINANCES OF THE BOROUGH OF BOUND BROOK

BE IT ORDAINED, by the Mayor and Council of the Borough of Bound Brook, County of Somerset, State of New Jersey, as follows:

SECTION 1. Section 21-15, "Stormwater Control" of the Revised General Ordinances of the Borough of Bound Brook is hereby repealed and replaced as the following:

Scope and Purpose:

A. Policy Statement

Flood control, groundwater recharge, and pollutant reduction shall be achieved through the use of stormwater management measures, including green infrastructure Best Management Practices (GI BMPs) and nonstructural stormwater management strategies. GI BMPs and low impact development (LID) should be utilized to meet the goal of maintaining natural hydrology to reduce stormwater runoff volume, reduce erosion, encourage infiltration and groundwater recharge, and reduce pollution. GI BMPs and LID should be developed based upon physical site conditions and the origin, nature and the anticipated quantity, or amount, of potential pollutants. Multiple stormwater management BMPs may be necessary to achieve the established performance standards for water quality, quantity, and groundwater recharge.

B. Purpose

The purpose of this ordinance is to establish minimum stormwater management requirements and controls for "major development," as defined below in Section II.

C. Applicability

- 1. This ordinance shall be applicable to the following major developments:
 - a. Non-residential major developments; and
 - b. Aspects of residential major developments that are not pre-empted by the Residential Site Improvement Standards at N.J.A.C. 5:21.
- 2. This ordinance shall also be applicable to all major developments undertaken by [insert name of municipality].
- D. Compatibility with Other Permit and Ordinance Requirements

Development approvals issued pursuant to this ordinance are to be considered an integral part of development approvals and do not relieve the applicant of the responsibility to secure required permits or approvals for activities regulated by any other applicable code, rule, act, or ordinance. In their interpretation and application, the provisions of this ordinance shall be held to be the minimum requirements for the promotion of the public health, safety, and general welfare.

This ordinance is not intended to interfere with, abrogate, or annul any other ordinances, rule or regulation, statute, or other provision of law except that, where any provision of this ordinance imposes restrictions different from those imposed by any other ordinance, rule or regulation, or other provision of law, the more restrictive provisions or higher standards shall control.

Definitions:

For the purpose of this ordinance, the following terms, phrases, words and their derivations shall have the meanings stated herein unless their use in the text of this Chapter clearly demonstrates a different meaning. When not inconsistent with the context, words used in the present tense include the future, words used in the plural number include the singular number, and words used in the singular number include the plural number. The word "shall" is always mandatory and not merely directory. The definitions below are the same as or based on the corresponding definitions in the Stormwater Management Rules at N.J.A.C. 7:8-1.2.

"CAFRA Centers, Cores or Nodes" means those areas with boundaries incorporated by reference or revised by the Department in accordance with N.J.A.C. 7:7-13.16.

"CAFRA Planning Map" means the map used by the Department to identify the location of Coastal Planning Areas, CAFRA centers, CAFRA cores, and CAFRA nodes. The CAFRA Planning Map is available on the Department's Geographic Information System (GIS).

"Community basin" means an infiltration system, sand filter designed to infiltrate, standard constructed wetland, or wet pond, established in accordance with N.J.A.C. 7:8-4.2(c)14, that is designed and constructed in accordance with the New Jersey Stormwater Best Management Practices Manual, or an alternate design, approved in accordance with N.J.A.C. 7:8-5.2(g), for an infiltration system, sand filter designed to infiltrate, standard constructed wetland, or wet pond and that complies with the requirements of this chapter.

"Compaction" means the increase in soil bulk density.

"Contributory drainage area" means the area from which stormwater runoff drains to a stormwater management measure, not including the area of the stormwater management measure itself.

"Core" means a pedestrian-oriented area of commercial and civic uses serving the surrounding municipality, generally including housing and access to public transportation. "County review agency" means an agency designated by the County Commissioners to review municipal stormwater management plans and implementing ordinance(s). The county review agency may either be:

- 1. A county planning agency or
- 2. A county water resource association created under N.J.S.A 58:16A-55.5, if the ordinance or resolution delegates authority to approve, conditionally approve, or disapprove municipal stormwater management plans and implementing ordinances.

"Department" means the Department of Environmental Protection.

"Designated Center" means a State Development and Redevelopment Plan Center as designated by the State Planning Commission such as urban, regional, town, village, or hamlet.

"Design engineer" means a person professionally qualified and duly licensed in New Jersey to perform engineering services that may include, but not necessarily be limited to, development of project requirements, creation and development of project design and preparation of drawings and specifications.

"Development" means the division of a parcel of land into two or more parcels, the construction, reconstruction, conversion, structural alteration, relocation or enlarge-enlargement of any building or structure, any mining excavation or landfill, and any use or change in the use of any building or other structure, or land or extension of use of land, for which permission is required under the Municipal Land Use Law, N.J.S.A. 40:55D-1 *et seq*.

In the case of development of agricultural land, development means: any activity that requires a State permit, any activity reviewed by the County Agricultural Board (CAB) and the State Agricultural Development Committee (SADC), and municipal review of any activity not exempted by the Right to Farm Act, N.J.S.A 4:1C-1 et seq.

"Disturbance" means the placement or reconstruction of impervious surface or motor vehicle surface, or exposure and/or movement of soil or bedrock or clearing, cutting, or removing of vegetation. Milling and repaving is not considered disturbance for the purposes of this definition.

"Drainage area" means a geographic area within which stormwater, sediments, or dissolved materials drain to a particular receiving waterbody or to a particular point along a receiving waterbody.

"Environmentally constrained area" means the following areas where the physical alteration of the land is in some way restricted, either through regulation, easement, deed restriction or ownership such as: wetlands, floodplains, threatened and endangered species sites or designated habitats, and parks and preserves. Habitats of endangered or threatened species are identified using the Department's Landscape Project as approved by the Department's Endangered and Nongame Species Program.

"Environmentally critical area" means an area or feature which is of significant environmental value, including but not limited to: stream corridors, natural heritage priority sites, habitats of endangered or threatened species, large areas of contiguous open space or upland forest, steep slopes, and well head protection and groundwater recharge areas. Habitats of endangered or threatened species are identified using the Department's Landscape Project as approved by the Department's Endangered and Nongame Species Program.

"Empowerment Neighborhoods" means neighborhoods designated by the Urban Coordinating Council "in consultation and conjunction with" the New Jersey Redevelopment Authority pursuant to N.J.S.A 55:19-69.

"Erosion" means the detachment and movement of soil or rock fragments by water, wind, ice, or gravity.

"Green infrastructure" means a stormwater management measure that manages stormwater close to its source by:

- 1. Treating stormwater runoff through infiltration into subsoil;
- 2. Treating stormwater runoff through filtration by vegetation or soil; or
- 3. Storing stormwater runoff for reuse.

"HUC 14" or "hydrologic unit code 14" means an area within which water drains to a particular receiving surface water body, also known as a subwatershed, which is identified by a 14-digit hydrologic unit boundary designation, delineated within New Jersey by the United States Geological Survey.

"Impervious surface" means a surface that has been covered with a layer of material so that it is highly resistant to infiltration by water.

"Infiltration" is the process by which water seeps into the soil from precipitation.

"Lead planning agency" means one or more public entities having stormwater management planning authority designated by the regional stormwater management planning committee pursuant to N.J.A.C. 7:8-3.2, that serves as the primary representative of the committee.

"Major development" means an individual "development," as well as multiple developments that individually or collectively result in:

- 1. The disturbance of one or more acres of land since February 2, 2004;
- 2. The creation of one-quarter acre or more of "regulated impervious surface" since February 2, 2004;

The creation of one-quarter acre or more of "regulated motor vehicle surface" since March 2, 2021 {or the effective date of this ordinance, whichever is earlier}; or

3. A combination of 2 and 3 above that totals an area of one-quarter acre or more. The same surface shall not be counted twice when determining if the combination area equals one-quarter acre or more.

Major development includes all developments that are part of a common plan of development or sale (for example, phased residential development) that collectively or individually meet any one or more of paragraphs 1, 2, 3, or 4 above. Projects undertaken by any government agency that otherwise meet the definition of "major development" but which do not require approval under the Municipal Land Use Law, N.J.S.A. 40:55D-1 et seq., are also considered "major development."

NOTE: The definition of major development above aligns with the definition at N.J.A.C. 7:8-1.2 and is recommended for consistency. Alternatively, a municipality may adopt the following definition, which is the minimum standard required. Municipalities that have already adopted the definition at N.J.A.C. 7:8-1.2 or another definition that goes beyond the minimum requirement should not reduce the stringency of their definition by adopting the minimum standard.

"Major development" means an individual "development," as well as multiple developments that individually or collectively result in the disturbance of one or more acres of land since February 2, 2004.

Major development includes all developments that are part of a common plan of development or sale (for example, phased residential development) that collectively or individually result in the disturbance of one or more acres of land since February 2, 2004. Projects undertaken by any government agency that otherwise meet the definition of "major development" but which do not require approval under the Municipal Land Use Law, N.J.S.A. 40:55D-1 et seq., are also considered "major development."

Additionally, individual municipalities may define major development with a smaller area of disturbance, a smaller area of regulated impervious or motor vehicle surface, or both.

"Motor vehicle" means land vehicles propelled other than by muscular power, such as automobiles, motorcycles, autocycles, and low speed vehicles. For the purposes of this definition, motor vehicle does not include farm equipment, snowmobiles, all-terrain vehicles, motorized wheelchairs, go-carts, gas buggies, golf carts, ski-slope grooming machines, or vehicles that run only on rails or tracks.

"Motor vehicle surface" means any pervious or impervious surface that is intended to be used by "motor vehicles" and/or aircraft, and is directly exposed to precipitation including, but not limited to, driveways, parking areas, parking garages, roads, racetracks, and runways.

"Municipality" means any city, borough, town, township, or village.

"New Jersey Stormwater Best Management Practices (BMP) Manual" or "BMP Manual" means the manual maintained by the Department providing, in part, design specifications, removal rates, calculation methods, and soil testing procedures approved by the Department as being capable of contributing to the achievement of the stormwater management standards specified in this chapter. The BMP Manual is periodically amended by the Department as necessary to provide design specifications on additional best management practices and new information on already included practices reflecting the best available current information regarding the particular practice and the Department's determination as to the ability of that best management practice to contribute to compliance with the standards contained in this chapter. Alternative stormwater management measures, removal rates, or calculation methods may be utilized, subject to any limitations specified in this chapter, provided the design engineer demonstrates to the municipality, in accordance with Section IV.F. of this ordinance and N.J.A.C. 7:8-5.2(g), that the proposed measure and its design will contribute to achievement of the design and performance standards established by this chapter.

"Node" means an area designated by the State Planning Commission concentrating facilities and activities which are not organized in a compact form.

"Nutrient" means a chemical element or compound, such as nitrogen or phosphorus, which is essential to and promotes the development of organisms.

"Person" means any individual, corporation, company, partnership, firm, association, political subdivision of this State and any state, interstate or Federal agency.

"Pollutant" means any dredged spoil, solid waste, incinerator residue, filter backwash, sewage, garbage, refuse, oil, grease, sewage sludge, munitions, chemical wastes, biological materials, medical wastes, radioactive substance (except those regulated under the Atomic Energy Act of 1954, as amended (42 U.S.C. §§ 2011 *et seq.*)), thermal waste, wrecked or discarded equipment, rock, sand, cellar dirt, industrial, municipal, agricultural, and construction waste or runoff, or other residue discharged directly or indirectly to the land, ground waters or surface waters of the State, or to a domestic treatment works. "Pollutant" includes both hazardous and nonhazardous pollutants.

"Recharge" means the amount of water from precipitation that infiltrates into the ground and is not evapotranspired.

"Regulated impervious surface" means any of the following, alone or in combination:

- 1. A net increase of impervious surface;
- 2. The total area of impervious surface collected by a new stormwater conveyance system (for the purpose of this definition, a "new stormwater conveyance system" is a stormwater conveyance system that is constructed where one did not exist immediately prior to its construction or an existing system for which a new discharge location is created);
- 3. The total area of impervious surface proposed to be newly collected by an existing stormwater conveyance system; and/or
- 4. The total area of impervious surface collected by an existing stormwater conveyance system where the capacity of that conveyance system is increased.

"Regulated motor vehicle surface" means any of the following, alone or in combination:

- 1. The total area of motor vehicle surface that is currently receiving water;
- 2. A net increase in motor vehicle surface; and/or quality treatment either by vegetation or soil, by an existing stormwater management measure, or by treatment at a wastewater treatment plant, where the water quality treatment will be modified or removed.

"Sediment" means solid material, mineral or organic, that is in suspension, is being transported, or has been moved from its site of origin by air, water or gravity as a product of erosion.

"Site" means the lot or lots upon which a major development is to occur or has occurred.

"Soil" means all unconsolidated mineral and organic material of any origin.

"State Development and Redevelopment Plan Metropolitan Planning Area (PA1)" means an area delineated on the State Plan Policy Map and adopted by the State Planning Commission that is intended to be the focus for much of the State's future redevelopment and revitalization efforts.

"State Plan Policy Map" is defined as the geographic application of the State Development and Redevelopment Plan's goals and statewide policies, and the official map of these goals and policies.

"Stormwater" means water resulting from precipitation (including rain and snow) that runs off the land's surface, is transmitted to the subsurface, or is captured by separate storm sewers or other sewage or drainage facilities, or conveyed by snow removal equipment.

"Stormwater management BMP" means an excavation or embankment and related areas designed to retain stormwater runoff. A stormwater management BMP may either be normally dry (that is, a detention basin or infiltration

system), retain water in a permanent pool (a retention basin), or be planted mainly with wetland vegetation (most constructed stormwater wetlands).

"Stormwater management measure" means any practice, technology, process, program, or other method intended to control or reduce stormwater runoff and associated pollutants, or to induce or control the infiltration or groundwater recharge of stormwater or to eliminate illicit or illegal non-stormwater discharges into stormwater conveyances.

"Stormwater runoff" means water flow on the surface of the ground or in storm sewers, resulting from precipitation.

"Stormwater management planning agency" means a public body authorized by legislation to prepare stormwater management plans.

"Stormwater management planning area" means the geographic area for which a stormwater management planning agency is authorized to prepare stormwater management plans, or a specific portion of that area identified in a stormwater management plan prepared by that agency.

"Tidal Flood Hazard Area" means a flood hazard area in which the flood elevation resulting from the two-, 10-, or 100-year storm, as applicable, is governed by tidal flooding from the Atlantic Ocean. Flooding in a tidal flood hazard area may be contributed to, or influenced by, stormwater runoff from inland areas, but the depth of flooding generated by the tidal rise and fall of the Atlantic Ocean is greater than flooding from any fluvial sources. In some situations, depending upon the extent of the storm surge from a particular storm event, a flood hazard area may be tidal in the 100-year storm, but fluvial in more frequent storm events.

"Urban Coordinating Council Empowerment Neighborhood" means a neighborhood given priority access to State resources through the New Jersey Redevelopment Authority.

"Urban Enterprise Zones" means a zone designated by the New Jersey Enterprise Zone Authority pursuant to the New Jersey Urban Enterprise Zones Act, N.J.S.A. 52:27H-60 et. seq.

"Urban Redevelopment Area" is defined as previously developed portions of areas:

- 1. Delineated on the State Plan Policy Map (SPPM) as the Metropolitan Planning Area (PA1), Designated Centers, Cores or Nodes;
- 2. Designated as CAFRA Centers, Cores or Nodes;
- 3. Designated as Urban Enterprise Zones; and
- 4. Designated as Urban Coordinating Council Empowerment Neighborhoods.

"Water control structure" means a structure within, or adjacent to, a water, which intentionally or coincidentally alters the hydraulic capacity, the flood elevation resulting from the two-, 10-, or 100-year storm, flood hazard area limit, and/or floodway limit of the water. Examples of a water control structure may include a bridge, culvert, dam, embankment, ford (if above grade), retaining wall, and weir.

"Waters of the State" means the ocean and its estuaries, all springs, streams, wetlands, and bodies of surface or groundwater, whether natural or artificial, within the boundaries of the State of New Jersey or subject to its jurisdiction.

"Wetlands" or "wetland" means an area that is inundated or saturated by surface water or ground water at a frequency and duration sufficient to support, and that under normal circumstances does support, a prevalence of vegetation typically

adapted for life in saturated soil conditions, commonly known as hydrophytic vegetation.

Design and Performance Standards for Stormwater Management Measures

- A. Stormwater management measures for major development shall be designed to provide erosion control, groundwater recharge, stormwater runoff quantity control, and stormwater runoff quality treatment as follows:
 - 1. The minimum standards for erosion control are those established under the Soil and Sediment Control Act, N.J.S.A. 4:24-39 et seq., and implementing rules at N.J.A.C. 2:90.
 - 2. The minimum standards for groundwater recharge, stormwater quality, and stormwater runoff quantity shall be met by incorporating green infrastructure.
- B. The standards in this ordinance apply only to new major development and are intended to minimize the impact of stormwater runoff on water quality and water quantity in receiving water bodies and maintain groundwater recharge. The standards do not apply to new major development to the extent that alternative design and performance standards are applicable under a regional stormwater management plan or Water Quality Management Plan adopted in accordance with Department rules.

Note: Alternative standards shall provide at least as much protection from stormwater-related loss of groundwater recharge, stormwater quantity and water quality impacts of major development projects as would be provided under the standards in N.J.A.C. 7:8-5.

Stormwater Management Requirements for Major Development

A. The development shall incorporate a maintenance plan for the stormwater management measures incorporated into the design of a major development in accordance with Section X.

- B. Stormwater management measures shall avoid adverse impacts of concentrated flow on habitat for threatened and endangered species as documented in the Department's Landscape Project or Natural Heritage Database established under N.J.S.A. 13:1B-15.147 through 15.150, particularly *Helonias bullata* (swamp pink) and/or *Clemmys muhlnebergi* (bog turtle).
- C. The following linear development projects are exempt from the groundwater recharge, stormwater runoff quality, and stormwater runoff quantity requirements of Section IV.P, Q and R:
 - 1. The construction of an underground utility line provided that the disturbed areas are revegetated upon completion;
 - 2. The construction of an aboveground utility line provided that the existing conditions are maintained to the maximum extent practicable; and
 - 3. The construction of a public pedestrian access, such as a sidewalk or trail with a maximum width of 14 feet, provided that the access is made of permeable material.
- D. A waiver from strict compliance from the green infrastructure, groundwater recharge, stormwater runoff quality, and stormwater runoff quantity requirements of Section IV.O, P, Q and R may be obtained for the enlargement of an existing public roadway or railroad; or the construction or enlargement of a public pedestrian access, provided that the following conditions are met:
 - 1. The applicant demonstrates that there is a public need for the project that cannot be accomplished by any other means;
 - 2. The applicant demonstrates through an alternatives analysis, that through the use of stormwater management measures, the option selected complies with the requirements of Section IV.O, P, Q and R to the maximum extent practicable;
 - 3. The applicant demonstrates that, in order to meet the requirements of Section IV.O, P, Q and R, existing structures currently in use, such as homes and buildings, would need to be condemned; and
 - 4. The applicant demonstrates that it does not own or have other rights to areas, including the potential to obtain through condemnation lands not falling under IV.D.3 above within the upstream drainage area of the receiving stream, that would provide additional opportunities to mitigate the requirements of Section IV.O, P, Q and R that were not achievable onsite.
- E. Tables 1 through 3 below summarize the ability of stormwater best management practices identified and described in the New Jersey Stormwater Best Management Practices Manual to satisfy the green infrastructure, groundwater recharge, stormwater runoff quality and stormwater runoff quantity standards specified in Section IV.O, P, Q and R. When designed in accordance with the most current version of the New Jersey Stormwater Best Management Practices Manual, the stormwater management measures found at N.J.A.C. 7:8-5.2 (f) Tables 5-1, 5-2 and 5-3 and listed below in Tables 1, 2 and 3 are presumed to be capable of providing stormwater controls for the design and performance standards as outlined in the tables below. Upon

amendments of the New Jersey Stormwater Best Management Practices to reflect additions or deletions of BMPs meeting these standards, or changes in the presumed performance of BMPs designed in accordance with the New Jersey Stormwater BMP Manual, the Department shall publish in the New Jersey Registers a notice of administrative change revising the applicable table. The most current version of the BMP Manual can be found on the Department's website at:

https://njstormwater.org/bmp_manual2.htm.

F. Where the BMP tables in the NJ Stormwater Management Rule are different due to updates or amendments with the tables in this ordinance the BMP Tables in the Stormwater Management rule at N.J.A.C. 7:8-5.2(f) shall take precedence.

| Table 1 Green Infrastructure BMPs for Groundwater Recharge, Stormwater Runoff Quality, and/or Stormwater Runoff Quantity | | | | | |
|--|--|----------------------------------|---|--|--|
| Best Management Practice | Stormwater Runoff Quality TSS Removal Rate (percent) | Stormwater Runoff Quantity | Groundwater Recharge | Minimum Separation from Seasonal High Water Table (feet) | |
| <u>Cistern</u> | <u>0</u> | <u>Yes</u> | <u>No</u> | = | |
| Dry Well ^(a) | <u>0</u> | <u>No</u> | <u>Yes</u> | <u>2</u> | |
| <u>Grass Swale</u> | 50 or less | <u>No</u> | <u>No</u> | 2 ^(e) 1 ^(f) | |
| Green Roof | <u>0</u> | Yes | <u>No</u> | == | |
| Manufactured Treatment Device(a) (g) | <u>50 or 80</u> | <u>No</u> | <u>No</u> | <u>Dependent</u> <u>upon the</u> <u>device</u> | |
| Pervious Paving System(a) | <u>80</u> | <u>Yes</u> | Yes ^(b) No ^(c) | 2 ^(b) 1 ^(c) | |
| Small-Scale Bioretention Basin ^(a) | <u>80 or 90</u> | <u>Yes</u> | Yes ^(b) No ^(c) | 2 ^(b) 1 ^(c) | |
| Small-Scale Infiltration Basin ^(a) | <u>80</u> | <u>Yes</u> | Yes | <u>2</u> | |
| Small-Scale Sand Filter | <u>80</u> | <u>Yes</u> | <u>Yes</u> | 2 | |

| <u>Vegetative</u> | 60-80 | <u>No</u> | <u>No</u> | <u></u> |
|---------------------|-------|-----------|-----------|---------|
| <u>Filter Strip</u> | | | | |

(Notes corresponding to annotations ^(a) through ^(g) are found on Page D-15

Table 2 Green Infrastructure BMPs for Stormwater Runoff Quantity (or for Groundwater Recharge and/or Stormwater Runoff Quality with a Waiver or Variance from N.J.A.C. 7:8-5.3)

| Best Management Practice | Stormwater Runoff Quality TSS Removal Rate (percent) | Stormwater Runoff Quantity | Groundwater Recharge | Minimum Separation from Seasonal High Water Table (feet) |
|------------------------------------|--|----------------------------|---|--|
| Bioretention System | <u>80 or 90</u> | <u>Yes</u> | Yes ^(b) No ^(c) | <u>2^(b)</u> <u>1^(c)</u> |
| Infiltration Basin | <u>80</u> | <u>Yes</u> | <u>Yes</u> | 2 |
| Sand Filter ^(b) | <u>80</u> | <u>Yes</u> | <u>Yes</u> | <u>2</u> |
| Standard Constructed Wetland | <u>90</u> | <u>Yes</u> | <u>No</u> | N/A |
| Wet Pond ^(d) | 50-90 | <u>Yes</u> | <u>No</u> | N/A |

(Notes corresponding to annotations (b) through (d) are found on Page D-15)

Table 3 BMPs for Groundwater Recharge, Stormwater Runoff Quality, and/or Stormwater Runoff Quantity only with a Waiver or Variance from N.J.A.C. 7:8-5.3

| Best Management Practice | Stormwater Runoff Quality TSS Removal Rate (percent) | Stormwater Runoff Quantity | Groundwater Recharge | Minimum Separation from Seasonal High Water Table (feet) |
|--|--|----------------------------|-------------------------|--|
| Blue Roof | <u>0</u> | Yes | <u>No</u> | <u>N/A</u> |
| Extended Detention Basin | 40-60 | <u>Yes</u> | <u>No</u> | <u>1</u> |
| Manufactured Treatment Device ^(h) | <u>50 or 80</u> | <u>No</u> | <u>No</u> | Dependent upon the device |
| Sand Filter ^(c) | <u>80</u> | Yes | <u>No</u> | <u>1</u> |
| Subsurface Gravel Wetland | <u>90</u> | <u>No</u> | <u>No</u> | 1 |
| Wet Pond | <u>50-90</u> | Yes | <u>No</u> | <u>N/A</u> |

Notes to Tables 1, 2, and 3:

- (a) subject to the applicable contributory drainage area limitation specified at Section IV.O.2;
- (b) designed to infiltrate into the subsoil;
- (c) designed with underdrains;
- (d) designed to maintain at least a 10-foot wide area of native vegetation along at least 50 percent of the shoreline and to include a stormwater runoff retention component designed to capture stormwater runoff for beneficial reuse, such as irrigation;
- (e) designed with a slope of less than two percent;
- (f) designed with a slope of equal to or greater than two percent;
- (g) manufactured treatment devices that meet the definition of green infrastructure at Section II;
- (h) manufactured treatment devices that do not meet the definition of green infrastructure at Section II.
- G. An alternative stormwater management measure, alternative removal rate, and/or alternative method to calculate the removal rate may be used if the design engineer demonstrates the capability of the proposed alternative stormwater management measure and/or the validity of the alternative rate or method to the municipality. A copy of any approved alternative stormwater management measure, alternative removal rate, and/or alternative method to calculate the removal rate shall be provided to the Department in accordance with Section VI.B. Alternative stormwater management measures may be used to satisfy the

requirements at Section IV.O only if the measures meet the definition of green infrastructure at Section II. Alternative stormwater management measures that function in a similar manner to a BMP listed at Section O.2 are subject to the contributory drainage area limitation specified at Section O.2 for that similarly functioning BMP. Alternative stormwater management measures approved in accordance with this subsection that do not function in a similar manner to any BMP listed at Section O.2 shall have a contributory drainage area less than or equal to 2.5 acres, except for alternative stormwater management measures that function similarly to cisterns, grass swales, green roofs, standard constructed wetlands, vegetative filter strips, and wet ponds, which are not subject to a contributory drainage area limitation. Alternative measures that function similarly to standard constructed wetlands or wet ponds shall not be used for compliance with the stormwater runoff quality standard unless a variance in accordance with N.J.A.C. 7:8-4.6 or a waiver from strict compliance in accordance with Section IV.D is granted from Section IV.O.

- H. Whenever the stormwater management design includes one or more BMPs that will infiltrate stormwater into subsoil, the design engineer shall assess the hydraulic impact on the groundwater table and design the site, so as to avoid adverse hydraulic impacts. Potential adverse hydraulic impacts include, but are not limited to, exacerbating a naturally or seasonally high water table, so as to cause surficial ponding, flooding of basements, or interference with the proper operation of subsurface sewage disposal systems or other subsurface structures within the zone of influence of the groundwater mound, or interference with the proper functioning of the stormwater management measure itself.
- I. Design standards for stormwater management measures are as follows:
 - 1. Stormwater management measures shall be designed to take into account the existing site conditions, including, but not limited to, environmentally critical areas; wetlands; flood-prone areas; slopes; depth to seasonal high water table; soil type, permeability, and texture; drainage area and drainage patterns; and the presence of solution-prone carbonate rocks (limestone); Stormwater management measures shall be designed to minimize maintenance, facilitate maintenance and repairs, and ensure proper functioning. Trash racks shall be installed at the intake to the outlet structure, as appropriate, and shall have parallel bars with one-inch spacing between the bars to the elevation of the water quality design storm. For elevations higher than the water quality design storm, the parallel bars at the outlet structure shall be spaced no greater than one-third the width of the diameter of the orifice or one-third the width of the weir, with a minimum spacing between bars of one inch and a maximum spacing between bars of six inches. In addition, the design of trash racks must comply with the requirements of Section VIII.C;
 - 2. Stormwater management measures shall be designed, constructed, and installed to be strong, durable, and corrosion resistant. Measures that are consistent with the relevant portions of the Residential Site Improvement Standards at N.J.A.C. 5:21-7.3, 7.4, and 7.5 shall be deemed to meet this requirement;

- 3. Stormwater management BMPs shall be designed to meet the minimum safety standards for stormwater management BMPs at Section VIII; and
- 4. The size of the orifice at the intake to the outlet from the stormwater management BMP shall be a minimum of two and one-half inches in diameter.
- J. Manufactured treatment devices may be used to meet the requirements of this subchapter, provided the pollutant removal rates are verified by the New Jersey Corporation for Advanced Technology and certified by the Department. Manufactured treatment devices that do not meet the definition of green infrastructure at Section II may be used only under the circumstances described at Section IV.O.4.
- K. Any application for a new agricultural development that meets the definition of major development at Section II shall be submitted to the Soil Conservation District for review and approval in accordance with the requirements at Sections IV.O, P, Q and R and any applicable Soil Conservation District guidelines for stormwater runoff quantity and erosion control. For purposes of this subsection, "agricultural development" means land uses normally associated with the production of food, fiber, and livestock for sale. Such uses do not include the development of land for the processing or sale of food and the manufacture of agriculturally related products.
- L. If there is more than one drainage area, the groundwater recharge, stormwater runoff quality, and stormwater runoff quantity standards at Section IV.P, Q and R shall be met in each drainage area, unless the runoff from the drainage areas converge onsite and no adverse environmental impact would occur as a result of compliance with any one or more of the individual standards being determined utilizing a weighted average of the results achieved for that individual standard across the affected drainage areas.
- M. Any stormwater management measure authorized under the municipal stormwater management plan or ordinance shall be reflected in a deed notice recorded in the {insert Office of the County Clerk or the registrar of deeds and mortgages of the county in which the development, project, project site, or mitigation area containing the stormwater management measure is located, as appropriate, to the municipality. A form of deed notice shall be submitted to the municipality for approval prior to filing. The deed notice shall contain a description of the stormwater management measure(s) used to meet the green infrastructure, groundwater recharge, stormwater runoff quality, and stormwater runoff quantity standards at Section IV.O, P, Q and R and shall identify the location of the stormwater management measure(s) in NAD 1983 State Plane New Jersey FIPS 2900 US Feet or Latitude and Longitude in decimal degrees. The deed notice shall also reference the maintenance plan required to be recorded upon the deed pursuant to Section X.B.5. Prior to the commencement of construction, proof that the above required deed notice has been filed shall be submitted to the municipality. Proof that the required information has been recorded on the deed shall be in the form of either a copy of the complete recorded document or a receipt from the clerk or other proof of recordation

provided by the recording office. However, if the initial proof provided to the municipality is not a copy of the complete recorded document, a copy of the complete recorded document shall be provided to the municipality within 180 calendar days of the authorization granted by the municipality.

N. A stormwater management measure approved under the municipal stormwater management plan or ordinance may be altered or replaced with the approval of the municipality, if the municipality determines that the proposed alteration or replacement meets the design and performance standards pursuant to Section IV of this ordinance and provides the same level of stormwater management as the previously approved stormwater management measure that is being altered or replaced. If an alteration or replacement is approved, a revised deed notice shall be submitted to the municipality for approval and subsequently recorded with the {insert appropriate Office of the County Clerk or the registrar of deeds and mortgages, as applies} and shall contain a description and location of the stormwater management measure, as well as reference to the maintenance plan, in accordance with M above. Prior to the commencement of construction, proof that the above required deed notice has been filed shall be submitted to the municipality in accordance with M above.

O. Green Infrastructure Standards

- 1. This subsection specifies the types of green infrastructure BMPs that may be used to satisfy the groundwater recharge, stormwater runoff quality, and stormwater runoff quantity standards.
- 2. To satisfy the groundwater recharge and stormwater runoff quality standards at Section IV.P and Q, the design engineer shall utilize green infrastructure BMPs identified in Table 1 at Section IV.F. and/or an alternative stormwater management measure approved in accordance with Section IV.G. The following green infrastructure BMPs are subject to the following maximum contributory drainage area limitations:

| Best Management | Maximum Contributory | | |
|--------------------------------|--|--|--|
| Practice | <u>Drainage Area</u> | | |
| <u>Dry Well</u> | <u>1 acre</u> | | |
| Manufactured Treatment Device | <u>2.5 acres</u> | | |
| Pervious Pavement Systems | Area of additional inflow cannot exceed three times the area occupied by the BMP | | |
| Small-scale Bioretention | <u>2.5 acres</u> | | |
| Small-scale Infiltration Basin | <u>2.5 acres</u> | | |
| Small-scale Sand Filter | <u>2.5 acres</u> | | |

- 3. To satisfy the stormwater runoff quantity standards at Section IV.R, the design engineer shall utilize BMPs from Table 1 or from Table 2 and/or an alternative stormwater management measure approved in accordance with Section IV.G.
- 4. If a variance in accordance with N.J.A.C. 7:8-4.6 or a waiver from strict compliance in accordance with Section IV.D is granted from the requirements of this subsection, then BMPs from Table 1, 2, or 3, and/or an alternative stormwater management measure approved in accordance with Section IV.G may be used to meet the groundwater recharge, stormwater runoff quality, and stormwater runoff quantity standards at Section IV.P, Q and R.
- 5. For separate or combined storm sewer improvement projects, such as sewer separation, undertaken by a government agency or public utility (for example, a sewerage company), the requirements of this subsection shall only apply to areas owned in fee simple by the government agency or utility, and areas within a right-of-way or easement held or controlled by the government agency or utility; the entity shall not be required to obtain additional property or property rights to fully satisfy the requirements of this subsection. Regardless of the amount of area of a separate or combined storm sewer improvement project subject to the green infrastructure requirements of this subsection, each project shall fully comply with the applicable groundwater recharge, stormwater runoff quality control, and stormwater runoff quantity standards at Section IV.P, Q and R, unless the project is granted a waiver from strict compliance in accordance with Section IV.D.

P. Groundwater Recharge Standards

- 1. This subsection contains the minimum design and performance standards for groundwater recharge as follows:
- 2. The design engineer shall, using the assumptions and factors for stormwater runoff and groundwater recharge calculations at Section V, either:
 - i. Demonstrate through hydrologic and hydraulic analysis that the site and its stormwater management measures maintain 100 percent of the average annual pre-construction groundwater recharge volume for the site; or
 - ii. Demonstrate through hydrologic and hydraulic analysis that the increase of stormwater runoff volume from pre-construction to post-construction for the 2-year storm is infiltrated.
- 3. This groundwater recharge requirement does not apply to projects within the "urban redevelopment area," or to projects subject to 4 below.
- 4. The following types of stormwater shall not be recharged:
 - i. Stormwater from areas of high pollutant loading. High pollutant loading areas are areas in industrial and commercial developments where solvents and/or petroleum products are loaded/unloaded, stored, or applied, areas where pesticides are loaded/unloaded or stored; areas where hazardous

- materials are expected to be present in greater than "reportable quantities" as defined by the United States Environmental Protection Agency (EPA) at 40 CFR 302.4; areas where recharge would be inconsistent with Department approved remedial action work plan or landfill closure plan and areas with high risks for spills of toxic materials, such as gas stations and vehicle maintenance facilities; and
- ii. Industrial stormwater exposed to "source material." "Source material" means any material(s) or machinery, located at an industrial facility, that is directly or indirectly related to process, manufacturing or other industrial activities, which could be a source of pollutants in any industrial stormwater discharge to groundwater. Source materials include, but are not limited to, raw materials; intermediate products; final products; waste materials; by-products; industrial machinery and fuels, and lubricants, solvents, and detergents that are related to process, manufacturing, or other industrial activities that are exposed to stormwater.

Q. Stormwater Runoff Quality Standards

- 1. This subsection contains the minimum design and performance standards to control stormwater runoff quality impacts of major development. Stormwater runoff quality standards are applicable when the major development results in an increase of one-quarter acre or more of regulated motor vehicle surface.
- 2. Stormwater management measures shall be designed to reduce the post-construction load of total suspended solids (TSS) in stormwater runoff generated from the water quality design storm as follows:
 - i. Eighty percent TSS removal of the anticipated load, expressed as an annual average shall be achieved for the stormwater runoff from the net increase of motor vehicle surface.
 - ii. If the surface is considered regulated motor vehicle surface because the water quality treatment for an area of motor vehicle surface that is currently receiving water quality treatment either by vegetation or soil, by an existing stormwater management measure, or by treatment at a wastewater treatment plant is to be modified or removed, the project shall maintain or increase the existing TSS removal of the anticipated load expressed as an annual average.
- 3. The requirement to reduce TSS does not apply to any stormwater runoff in a discharge regulated under a numeric effluent limitation for TSS imposed under the New Jersey Pollutant Discharge Elimination System (NJPDES) rules, N.J.A.C. 7:14A, or in a discharge specifically exempt under a NJPDES permit from this requirement. Every major development, including any that discharge into a combined sewer system, shall comply with 2 above, unless the major development is itself subject to a NJPDES permit with a numeric effluent limitation for TSS or the NJPDES permit to which the major development is subject exempts the development from a numeric effluent limitation for TSS.

4. The water quality design storm is 1.25 inches of rainfall in two hours. Water quality calculations shall take into account the distribution of rain from the water quality design storm, as reflected in Table 4, below. The calculation of the volume of runoff may take into account the implementation of stormwater management measures.

Table 4 - Water Quality Design Storm Distribution

| Table 4 - Water Quanty Design Storm Distribution | | | | | | | |
|--|---|----------------------------|--|---------------------------------|--|--|--|
| _ | Cumulative | _ | Cumulative | _ | Cumulative | | |
| Time | Rainfall | Time | Rainfall | Time | Rainfall | | |
| (Minutes) | (Inches) | (Minutes) | (Inches) | (Minutes) | (Inches) | | |
| 1 | 0.00166 | 41 | 0.1728 | 81 | 1.0906 | | |
| 2 | 0.00332 | 42 | 0.1796 | 82 | 1.0972 | | |
| 3 | 0.00498 | 43 | 0.1864 | 83 | 1.1038 | | |
| 4 | 0.00664 | 44 | 0.1932 | 84 | 1.1104 | | |
| 5 | 0.00830 | 45 | 0.2000 | 85 | 1.1170 | | |
| 6 | 0.00996 | 46 | 0.2117 | 86 | 1.1236 | | |
| 7 | 0.01162 | 47 | 0.2233 | 87 | 1.1302 | | |
| 8 | 0.01328 | 48 | 0.2350 | 88 | 1.1368 | | |
| 9 | 0.01494 | 49 | 0.2466 | 89 | 1.1434 | | |
| 10 | 0.01660 | 50 | 0.2583 | 90 | 1.1500 | | |
| 11 | 0.01828 | 51 | 0.2783 | 91 | 1.1550 | | |
| 12 | 0.01996 | 52 | 0.2983 | 92 | 1.1600 | | |
| 13 | 0.02164 | 53 | 0.3183 | 93 | 1.1650 | | |
| 14 | 0.02332 | 54 | 0.3383 | 94 | 1.1700 | | |
| 15 | 0.02500 | 55 | 0.3583 | 95 | 1.1750 | | |
| 16 | 0.03000 | 56 | 0.4116 | 96 | 1.1800 | | |
| 17 | 0.03500 | 57 | 0.4650 | 97 | 1.1850 | | |
| 18 | 0.04000 | 58 | 0.5183 | 98 | 1.1900 | | |
| 19 | 0.04500 | 59 | 0.5717 | 99 | 1.1950 | | |
| 20 | 0.05000 | 60 | 0.6250 | 100 | 1.2000 | | |
| 21 | 0.05500 | 61 | 0.6783 | 101 | 1.2050 | | |
| 22 | 0.06000 | 62 | 0.7317 | 102 | 1.2100 | | |
| 23 | 0.06500 | 63 | 0.7850 | 103 | 1.2150 | | |
| 24 | 0.07000 | 64 | 0.8384 | 104 | 1.2200 | | |
| 25 | 0.07500 | 65 | 0.8917 | 105 | 1.2250 | | |
| 26 | 0.08000 | 66 | 0.9117 | 106 | 1.2267 | | |
| 27 | 0.08500 | 67 | 0.9317 | 107 | 1.2284 | | |
| 28 | 0.09000 | 68 | 0.9517 | 108 | 1.2300 | | |
| 29 | 0.09500 | 69 | 0.9717 | 109 | 1.2317 | | |
| 30 | 0.10000 | 70 | 0.9917 | 110 | 1.2334 | | |
| 31 | 0.10660 | 71 | 1.0034 | 111 | 1.2351 | | |
| 32 | 0.11320 | 72 | 1.0150 | 112 | 1.2367 | | |
| 33 | 0.11980 | 73 | 1.0267 | 113 | 1.2384 | | |
| 34 | 0.12640 | 74 | 1.0383 | 114 | 1.2400 | | |
| 35 | 0.13300 | 75 | 1.0500 | 115 | 1.2417 | | |
| 36 | | | 1.0568 | | | | |
| | | 77 | | | | | |
| 38 | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| 37 | 0.13960 0.14620 0.15280 0.15940 0.16600 | 76 77 78 79 80 | 1.0568 1.0636 1.0704 1.0772 1.0840 | 116 117 118 119 120 | 1.2434 1.2450 1.2467 1.2483 1.2500 | | |

5. If more than one BMP in series is necessary to achieve the required 80 percent TSS reduction for a site, the applicant shall utilize the following formula to calculate TSS reduction:

$$R = A + B - (A x B) / 100$$
, Where

R = total TSS Percent Load Removal from application of both BMPs, and

A = the TSS Percent Removal Rate applicable to the first BMP

B = the TSS Percent Removal Rate applicable to the second BMP.

- 6. Stormwater management measures shall also be designed to reduce, to the maximum extent feasible, the post-construction nutrient load of the anticipated load from the developed site in stormwater runoff generated from the water quality design storm. In achieving reduction of nutrients to the maximum extent feasible, the design of the site shall include green infrastructure BMPs that optimize nutrient removal while still achieving the performance standards in Section IV.P, Q and R.
- 7. In accordance with the definition of FW1 at N.J.A.C. 7:9B-1.4, stormwater management measures shall be designed to prevent any increase in stormwater runoff to waters classified as FW1.
- 8. The Flood Hazard Area Control Act Rules at N.J.A.C. 7:13-4.1(c)1 establish 300-foot riparian zones along Category One waters, as designated in the Surface Water Quality Standards at N.J.A.C. 7:9B, and certain upstream tributaries to Category One waters. A person shall not undertake a major development that is located within or discharges into a 300-foot riparian zone without prior authorization from the Department under N.J.A.C. 7:13.
- 9. Pursuant to the Flood Hazard Area Control Act Rules at N.J.A.C. 7:13-11.2(j)3.i, runoff from the water quality design storm that is discharged within a 300-foot riparian zone shall be treated in accordance with this subsection to reduce the post-construction load of total suspended solids by 95 percent of the anticipated load from the developed site, expressed as an annual average.
- 10. This stormwater runoff quality standards do not apply to the construction of one individual single-family dwelling, provided that it is not part of a larger development or subdivision that has received preliminary or final site plan approval prior to December 3, 2018, and that the motor vehicle surfaces are made of permeable material(s) such as gravel, dirt, and/or shells.

R. Stormwater Runoff Quantity Standards

- 1. This subsection contains the minimum design and performance standards to control stormwater runoff quantity impacts of major development.
- 2. In order to control stormwater runoff quantity impacts, the design engineer shall, using the assumptions and factors for stormwater runoff calculations at Section V, complete one of the following:

- i. Demonstrate through hydrologic and hydraulic analysis that for stormwater leaving the site, post-construction runoff hydrographs for the 2-, 10-, and 100-year storm events do not exceed, at any point in time, the pre-construction runoff hydrographs for the same storm events;
- ii. Demonstrate through hydrologic and hydraulic analysis that there is no increase, as compared to the pre-construction condition, in the peak runoff rates of stormwater leaving the site for the 2-, 10- and 100-year storm events and that the increased volume or change in timing of stormwater runoff will not increase flood damage at or downstream of the site. This analysis shall include the analysis of impacts of existing land uses and projected land uses assuming full development under existing zoning and land use ordinances in the drainage area;
- iii. Design stormwater management measures so that the post-construction peak runoff rates for the 2-, 10- and 100-year storm events are 50, 75 and 80 percent, respectively, of the pre-construction peak runoff rates. The percentages apply only to the post-construction stormwater runoff that is attributable to the portion of the site on which the proposed development or project is to be constructed; or
- iv. In tidal flood hazard areas, stormwater runoff quantity analysis in accordance with 2.i, ii and iii above is required unless the design engineer demonstrates through hydrologic and hydraulic analysis that the increased volume, change in timing, or increased rate of the stormwater runoff, or any combination of the three will not result in additional flood damage below the point of discharge of the major development. No analysis is required if the stormwater is discharged directly into any ocean, bay, inlet, or the reach of any watercourse between its confluence with an ocean, bay, or inlet and downstream of the first water control structure.
- 3. The stormwater runoff quantity standards shall be applied at the site's boundary to each abutting lot, roadway, watercourse, or receiving storm sewer system.

Calculation of Stormwater Runoff and Groundwater Recharge:

- A. Stormwater runoff shall be calculated in accordance with the following:
 - 1. The design engineer shall calculate runoff using one of the following methods:

The USDA Natural Resources Conservation Service (NRCS) methodology, including the NRCS Runoff Equation and Dimensionless Unit Hydrograph, as described in Chapters 7, 9, 10, 15 and 16 Part 630, Hydrology National Engineering Handbook, incorporated herein by reference as amended and supplemented. This methodology is additionally described in *Technical Release 55 - Urban Hydrology for Small Watersheds* (TR-55), dated June 1986, incorporated herein by reference as amended and supplemented. Information regarding the methodology is available from the Natural Resources Conservation Service website at:

https://www.nrcs.usda.gov/Internet/FSE DOCUMENTS/stelprdb1044171.pdf

or at United States Department of Agriculture Natural Resources Conservation Service, 220 Davison Avenue, Somerset, New Jersey 08873; or

i. The Rational Method for peak flow and the Modified Rational Method for hydrograph computations. The rational and modified rational methods are described in "Appendix A-9 Modified Rational Method" in the Standards for Soil Erosion and Sediment Control in New Jersey, January 2014. This document is available from the State Soil Conservation Committee or any of the Soil Conservation Districts listed at N.J.A.C. 2:90-1.3(a)3. The location, address, and telephone number for each Soil Conservation District is available from the State Soil Conservation Committee, PO Box 330, Trenton, New Jersey 08625. The document is also available at:

 $\underline{http://www.nj.gov/agriculture/divisions/anr/pdf/2014NJSoilErosionControlStandardsComplete.pdf.}$

- 2. For the purpose of calculating runoff coefficients and groundwater recharge, there is a presumption that the pre-construction condition of a site or portion thereof is a wooded land use with good hydrologic condition. The term "runoff coefficient" applies to both the NRCS methodology above at Section V.A.1.i and the Rational and Modified Rational Methods at Section V.A.1.ii. A runoff coefficient or a groundwater recharge land cover for an existing condition may be used on all or a portion of the site if the design engineer verifies that the hydrologic condition has existed on the site or portion of the site for at least five years without interruption prior to the time of application. If more than one land cover have existed on the site during the five years immediately prior to the time of application, the land cover with the lowest runoff potential shall be used for the computations. In addition, there is the presumption that the site is in good hydrologic condition (if the land use type is pasture, lawn, or park), with good cover (if the land use type is woods), or with good hydrologic condition and conservation treatment (if the land use type is cultivation).
- In computing pre-construction stormwater runoff, the design engineer shall account
 for all significant land features and structures, such as ponds, wetlands, depressions,
 hedgerows, or culverts, that may reduce pre-construction stormwater runoff rates and
 volumes.
 - In computing stormwater runoff from all design storms, the design engineer shall consider the relative stormwater runoff rates and/or volumes of pervious and impervious surfaces separately to accurately compute the rates and volume of stormwater runoff from the site. To calculate runoff from unconnected impervious cover, urban impervious area modifications as described in the NRCS *Technical Release* 55 *Urban Hydrology for Small Watersheds* or other methods may be employed.
- 4. If the invert of the outlet structure of a stormwater management measure is below the flood hazard design flood elevation as defined at N.J.A.C. 7:13, the design engineer shall take into account the effects of tailwater in the design of structural stormwater management measures.

B. Groundwater recharge may be calculated in accordance with the following:

The New Jersey Geological Survey Report GSR-32, A Method for Evaluating Groundwater-Recharge Areas in New Jersey, incorporated herein by reference as amended and supplemented. Information regarding the methodology is available from the New Jersey Stormwater Best Management Practices Manual; at the New Jersey Geological Survey website at:

https://www.nj.gov/dep/njgs/pricelst/gsreport/gsr32.pdf

or at New Jersey Geological and Water Survey, 29 Arctic Parkway, PO Box 420 Mail Code 29-01, Trenton, New Jersey 08625-0420.

Sources for Technical Guidance:

A. Technical guidance for stormwater management measures can be found in the documents listed below, which are available to download from the Department's website at:

http://www.nj.gov/dep/stormwater/bmp manual2.htm.

- 1. Guidelines for stormwater management measures are contained in the New Jersey Stormwater Best Management Practices Manual, as amended and supplemented. Information is provided on stormwater management measures such as, but not limited to, those listed in Tables 1, 2, and 3.
- 2. Additional maintenance guidance is available on the Department's website at: https://www.njstormwater.org/maintenance_guidance.htm.
- B. Submissions required for review by the Department should be mailed to:

The Division of Water Quality, New Jersey Department of Environmental Protection, Mail Code 401-02B, PO Box 420, Trenton, New Jersey 08625-0420.

Section VII. Solids and Floatable Materials Control Standards:

- A. Site design features identified under Section IV.F above, or alternative designs in accordance with Section IV.G above, to prevent discharge of trash and debris from drainage systems shall comply with the following standard to control passage of solid and floatable materials through storm drain inlets. For purposes of this paragraph, "solid and floatable materials" means sediment, debris, trash, and other floating, suspended, or settleable solids. For exemptions to this standard see Section VII.A.2 below.
 - 1. Design engineers shall use one of the following grates whenever they use a grate in pavement or another ground surface to collect stormwater from that surface into a storm drain or surface water body under that grate:
 - The New Jersey Department of Transportation (NJDOT) bicycle safe grate, which is described in Chapter 2.4 of the NJDOT Bicycle Compatible Roadways and Bikeways Planning and Design Guidelines; or

ii. A different grate, if each individual clear space in that grate has an area of no more than seven (7.0) square inches, or is no greater than 0.5 inches across the smallest dimension.

Examples of grates subject to this standard include grates in grate inlets, the grate portion (non-curb-opening portion) of combination inlets, grates on storm sewer manholes, ditch grates, trench grates, and grates of spacer bars in slotted drains. Examples of ground surfaces include surfaces of roads (including bridges), driveways, parking areas, bikeways, plazas, sidewalks, lawns, fields, open channels, and stormwater system floors used to collect stormwater from the surface into a storm drain or surface water body.

- iii. For curb-opening inlets, including curb-opening inlets in combination inlets, the clear space in that curb opening, or each individual clear space if the curb opening has two or more clear spaces, shall have an area of no more than seven (7.0) square inches, or be no greater than two (2.0) inches across the smallest dimension.
- 2. The standard in A.1. above does not apply:
 - i. Where each individual clear space in the curb opening in existing curbopening inlet does not have an area of more than nine (9.0) square inches;
 - ii. Where the municipality agrees that the standards would cause inadequate hydraulic performance that could not practicably be overcome by using additional or larger storm drain inlets;

Where flows from the water quality design storm as specified in N.J.A.C. 7:8 are conveyed through any device (e.g., end of pipe netting facility, manufactured treatment device, or a catch basin hood) that is designed, at a minimum, to prevent delivery of all solid and floatable materials that could not pass through one of the following:

- a. A rectangular space four and five-eighths (4.625) inches long and one and one-half (1.5) inches wide (this option does not apply for outfall netting facilities); or
- b. A bar screen having a bar spacing of 0.5 inches.

Note that these exemptions do not authorize any infringement of requirements in the Residential Site Improvement Standards for bicycle safe grates in new residential development (N.J.A.C. 5:21-4.18(b)2 and 7.4(b)1).

- iii. Where flows are conveyed through a trash rack that has parallel bars with one-inch (1 inch) spacing between the bars, to the elevation of the Water Quality Design Storm as specified in N.J.A.C. 7:8; or
- iv. Where the New Jersey Department of Environmental Protection determines, pursuant to the New Jersey Register of Historic Places Rules at N.J.A.C. 7:4-7.2(c), that action to meet this standard is an undertaking that constitutes an encroachment or will damage or destroy the New Jersey Register listed historic property.

Safety Standards for Stormwater Management Basins:

- A. This section sets forth requirements to protect public safety through the proper design and operation of stormwater management BMPs. This section applies to any new stormwater management BMP.
- B. The provisions of this section are not intended to preempt more stringent municipal or county safety requirements for new or existing stormwater management BMPs. Municipal and county stormwater management plans and ordinances may, pursuant to their authority, require existing stormwater management BMPs to be retrofitted to meet one or more of the safety standards in Section VIII.C.1, VIII.C.2, and VIII.C.3 for trash racks, overflow grates, and escape provisions at outlet structures.

C. Requirements for Trash Racks, Overflow Grates and Escape Provisions

- 1. A trash rack is a device designed to catch trash and debris and prevent the clogging of outlet structures. Trash racks shall be installed at the intake to the outlet from the Stormwater management BMP to ensure proper functioning of the BMP outlets in accordance with the following:
 - i. The trash rack shall have parallel bars, with no greater than six-inch spacing between the bars;

The trash rack shall be designed so as not to adversely affect the hydraulic performance of the outlet pipe or structure;

- ii. The average velocity of flow through a clean trash rack is not to exceed 2.5 feet per second under the full range of stage and discharge. Velocity is to be computed on the basis of the net area of opening through the rack; and
- iii. The trash rack shall be constructed of rigid, durable, and corrosion resistant material and designed to withstand a perpendicular live loading of 300 pounds per square foot.
- 2. An overflow grate is designed to prevent obstruction of the overflow structure. If an outlet structure has an overflow grate, such grate shall meet the following requirements:
 - i. The overflow grate shall be secured to the outlet structure but removable for emergencies and maintenance.
 - ii. The overflow grate spacing shall be no less than two inches across the smallest dimension
 - iii. The overflow grate shall be constructed and installed to be rigid, durable, and corrosion resistant, and shall be designed to withstand a perpendicular live loading of 300 pounds per square foot.
- 3. Stormwater management BMPs shall include escape provisions as follows:
 - i. If a stormwater management BMP has an outlet structure, escape provisions shall be incorporated in or on the structure. Escape provisions

include the installation of permanent ladders, steps, rungs, or other features that provide easily accessible means of egress from stormwater management BMPs. With the prior approval of the municipality pursuant to VIII.C, a free-standing outlet structure may be exempted from this requirement;

- ii. Safety ledges shall be constructed on the slopes of all new stormwater management BMPs having a permanent pool of water deeper than two and one-half feet. Safety ledges shall be comprised of two steps. Each step shall be four to six feet in width. One step shall be located approximately two and one-half feet below the permanent water surface, and the second step shall be located one to one and one-half feet above the permanent water surface. See VIII.E for an illustration of safety ledges in a stormwater management BMP; and
- iii. In new stormwater management BMPs, the maximum interior slope for an earthen dam, embankment, or berm shall not be steeper than three horizontal to one vertical.

D. Variance or Exemption from Safety Standard

A variance or exemption from the safety standards for stormwater management BMPs may be granted only upon a written finding by the municipality that the variance or exemption will not constitute a threat to public safety.

E. Safety Ledge Illustration

Elevation View -Basin Safety Ledge Configuration Safety Ledge, 4 to 6 feet in Width, Gently Sloped for Drainage Top of Ledge, Permanent 12 to 18 inches Water Level **Above Water Surface** Top of Ledge, 30 inches Safety Ledge, Below Water 4 to 6 feet in Width, Gently Sloped for Drainage Surface Stable Slope Only For Basins with Permanent Pool of Water Not to Scale

Requirements for a Site Development Stormwater Plan:

A. Submission of Site Development Stormwater Plan

1. Whenever an applicant seeks municipal approval of a development subject to this ordinance, the applicant shall submit all of the required components of the Checklist

for the Site Development Stormwater Plan at Section IX.C below as part of the submission of the application for approval.

- 2. The applicant shall demonstrate that the project meets the standards set forth in this ordinance.
- 3. The applicant shall submit [specify number] copies of the materials listed in the checklist for site development stormwater plans in accordance with Section IX.C of this ordinance.

B. Site Development Stormwater Plan Approval

The applicant's Site Development project shall be reviewed as a part of the review process by the municipal board or official from which municipal approval is sought. That municipal board or official shall consult the municipality's review engineer to determine if all of the checklist requirements have been satisfied and to determine if the project meets the standards set forth in this ordinance.

C. Submission of Site Development Stormwater Plan

The following information shall be required:

1. Topographic Base Map

The reviewing engineer may require upstream tributary drainage system information as necessary. It is recommended that the topographic base map of the site be submitted which extends a minimum of 200 feet beyond the limits of the proposed development, at a scale of 1"=200' or greater, showing 2-foot contour intervals. The map as appropriate may indicate the following: existing surface water drainage, shorelines, steep slopes, soils, erodible soils, perennial or intermittent streams that drain into or upstream of the Category One waters, wetlands and flood plains along with their appropriate buffer strips, marshlands and other wetlands, pervious or vegetative surfaces, existing man-made structures, roads, bearing and distances of property lines, and significant natural and manmade features not otherwise shown.

2. Environmental Site Analysis

A written and graphic description of the natural and man-made features of the site and its surroundings should be submitted. This description should include a discussion of soil conditions, slopes, wetlands, waterways and vegetation on the site. Particular attention should be given to unique, unusual, or environmentally sensitive features and to those that provide particular opportunities or constraints for development.

3. Project Description and Site Plans

A map (or maps) at the scale of the topographical base map indicating the location of existing and proposed buildings roads, parking areas, utilities, structural facilities for stormwater management and sediment control, and other permanent structures. The map(s) shall also clearly show areas where alterations will occur in the natural terrain and cover, including lawns and other landscaping, and seasonal high groundwater elevations. A written description of the site plan and justification for proposed changes in natural conditions shall also be provided.

4. Land Use Planning and Source Control Plan

This plan shall provide a demonstration of how the goals and standards of Sections III through V are being met. The focus of this plan shall be to describe how the site is being developed to meet the objective of controlling groundwater recharge, stormwater quality and stormwater quantity problems at the source by land management and source controls whenever possible.

5. Stormwater Management Facilities Map

The following information, illustrated on a map of the same scale as the topographic base map, shall be included:

- i. Total area to be disturbed, paved or built upon, proposed surface contours, land area to be occupied by the stormwater management facilities and the type of vegetation thereon, and details of the proposed plan to control and dispose of stormwater.
- ii. Details of all stormwater management facility designs, during and after construction, including discharge provisions, discharge capacity for each outlet at different levels of detention and emergency spillway provisions with maximum discharge capacity of each spillway.

6. Calculations

- i. Comprehensive hydrologic and hydraulic design calculations for the predevelopment and post-development conditions for the design storms specified in Section IV of this ordinance.
- ii. When the proposed stormwater management control measures depend on the hydrologic properties of soils or require certain separation from the seasonal high water table, then a soils report shall be submitted. The soils report shall be based on onsite boring logs or soil pit profiles. The number and location of required soil borings or soil pits shall be determined based on what is needed to determine the suitability and distribution of soils present at the location of the control measure.

7. Maintenance and Repair Plan

The design and planning of the stormwater management facility shall meet the maintenance requirements of Section X.

8. Waiver from Submission Requirements

The municipal official or board reviewing an application under this ordinance may, in consultation with the municipality's review engineer, waive submission of any of the requirements in Section IX.C.1 through IX.C.6 of this ordinance when it can be demonstrated that the information requested is impossible to obtain or it would create a hardship on the applicant to obtain and its absence will not materially affect the review process.

Maintenance and Repair:

A. Applicability

Projects subject to review as in Section I.C of this ordinance shall comply with the requirements of Section X.B and X.C.

B. General Maintenance

- 1. The design engineer shall prepare a maintenance plan for the stormwater management measures incorporated into the design of a major development.
- 2. The maintenance plan shall contain specific preventative maintenance tasks and schedules; cost estimates, including estimated cost of sediment, debris, or trash removal; and the name, address, and telephone number of the person or persons responsible for preventative and corrective maintenance (including replacement). The plan shall contain information on BMP location, design, ownership, maintenance tasks and frequencies, and other details as specified in Chapter 8 of the NJ BMP Manual, as well as the tasks specific to the type of BMP, as described in the applicable chapter containing design specifics.
- 3. If the maintenance plan identifies a person other than the property owner (for example, a developer, a public agency or homeowners' association) as having the responsibility for maintenance, the plan shall include documentation of such person's or entity's agreement to assume this responsibility, or of the owner's obligation to dedicate a stormwater management facility to such person under an applicable ordinance or regulation.
- 4. Responsibility for maintenance shall not be assigned or transferred to the owner or tenant of an individual property in a residential development or project, unless such owner or tenant owns or leases the entire residential development or project. The individual property owner may be assigned incidental tasks, such as weeding of a green infrastructure BMP, provided the individual agrees to assume these tasks; however, the individual cannot be legally responsible for all of the maintenance required.
- 5. If the party responsible for maintenance identified under Section X.B.3 above is not a public agency, the maintenance plan and any future revisions based on Section X.B.7 below shall be recorded upon the deed of record for each property on which the maintenance described in the maintenance plan must be undertaken.
 - Preventative and corrective maintenance shall be performed to maintain the functional parameters (storage volume, infiltration rates, inflow/outflow capacity, etc.).of the stormwater management measure, including, but not limited to, repairs or replacement to the structure; removal of sediment, debris, or trash; restoration of eroded areas; snow and ice removal; fence repair or replacement; restoration of vegetation; and repair or replacement of non-vegetated linings.
- 6. The party responsible for maintenance identified under Section X.B.3 above shall perform all of the following requirements:
 - i. maintain a detailed log of all preventative and corrective maintenance for the structural stormwater management measures incorporated into the

- design of the development, including a record of all inspections and copies of all maintenance-related work orders;
- ii. evaluate the effectiveness of the maintenance plan at least once per year and adjust the plan and the deed as needed; and
- iii. retain and make available, upon request by any public entity with administrative, health, environmental, or safety authority over the site, the maintenance plan and the documentation required by Section X.B.6 and B.7 above.
- 7. The requirements of Section X.B.3 and B.4 do not apply to stormwater management facilities that are dedicated to and accepted by the municipality or another governmental agency, subject to all applicable municipal stormwater general permit conditions, as issued by the Department.

Note: It may be appropriate to delete requirements in the maintenance and repair plan that are not applicable if the ordinance requires the facility to be dedicated to the municipality. If the municipality does not want to take this responsibility, the ordinance should require the posting of a two year maintenance guarantee in accordance with N.J.S.A. 40:55D-53. Maintenance and inspection guidance can be found on the Department's website at:

https://www.njstormwater.org/maintenance_guidance.htm.

- 8. In the event that the stormwater management facility becomes a danger to public safety or public health, or if it is in need of maintenance or repair, the municipality shall so notify the responsible person in writing. Upon receipt of that notice, the responsible person shall have fourteen (14) days to effect maintenance and repair of the facility in a manner that is approved by the municipal engineer or his designee. The municipality, in its discretion, may extend the time allowed for effecting maintenance and repair for good cause. If the responsible person fails or refuses to perform such maintenance and repair, the municipality or County may immediately proceed to do so and shall bill the cost thereof to the responsible person. Nonpayment of such bill may result in a lien on the property.
- C. Nothing in this subsection shall preclude the municipality in which the major development is located from requiring the posting of a performance or maintenance guarantee in accordance with N.J.S.A. 40:55D-53.

Penalties:

Any person who erects, constructs, alters, repairs, converts, maintains, or uses any building, structure of land in violation of this section shall be subject, upon conviction thereof, to a fine of not more than \$2,000, or incarceration for a period not to exceed 90 days or both such fine and imprisonment, in the discretion of the Municipal Judge.

SECTION 2. Severability:

Each section, subsection, sentence, clause and phrase of this Ordinance is declared to be an independent section, subsection, sentence, clause and phrase, and the finding or holding of any such portion of this Ordinance to be unconstitutional, void, or ineffective for any cause, or reason, shall not affect any other portion of this Ordinance.

SECTION 3. Effective Date:

This Ordinance shall be in full force and effect from and after its adoption and any publication as required by law.

Jasmine D. Mathis
Borough Clerk

By:

Mayor Robert Fazen

Date of Introduction: February 9, 2021 Date of Adoption: February 23, 2021

BOROUGH OF BOUND BROOK RESOLUTION 2021-035

RESOLUTION AUTHORIZING 2020 BUDGET TRANSFERS

WHEREAS, various 2020 bills have been presented for payment this year, which bills represent obligations of the prior fiscal year, and were not covered at the time of transfers between the 2020 budget in the last two months of 2020; and

WHEREAS, N.J.S.A. 40A:4-59 provides that all unexpended balances carried forward after close of the fiscal year are available, until lapsed at the close of the succeeding year, to meet specific claims, commitments or contracts incurred during the preceding fiscal year, and all transfers to be made from unexpended balances to those which are expected to be insufficient during the first three months of the succeeding year:

NOW, THEREFORE, BE IT RESOLVED by the Mayor and Council of the Borough of Bound Brook, County of Somerset, State of New Jersey that the transfer in the amount of \$34,600.00 be made between the 2020 Budget Appropriation Reserves as follows:

| Department | FROM | Department | TO |
|---------------------------|-------------|-----------------------------|-------------|
| General Administration SW | \$15,000.00 | General Administration-OE | \$2,500.00 |
| 01-2020-0120-0100 | | 01-2020-120-100- | |
| Municipal Clerk- SW | \$12,600.00 | Financial Administration OE | \$16,200.00 |
| 01-2020-0120-0120 | | 01-2020-0120-0130-2 | |
| Codification OE | 3,000.00 | Insurance-OE | \$3,200.00 |
| | | 01-2020-0123 | |
| Tax Collector SW | 4,000.00 | Solid Waste OE | \$5,000.00 |
| 01-2020-120-145- | | 01-2020-0126 | |
| | | Building & Grounds OE | \$5,000.00 |
| | | 01-2020-0126-0310-2 | |
| | | Utilities-Telephone | 2,700.00 |
| | | 01-2020-131 | |
| | | | |
| | | | |
| Totals | \$34,600.00 | Totals | \$34,600.00 |

| | Approved: |
|--|-----------------------|
| Attest: | Mayor Robert P. Fazen |
| Jasmine D. Mathis, Borough Clerk Date of Adoption: February 23, 2021 | |

RESOLUTION 2021-036

REQUESTING THAT SOMERSET COUNTY, THE STATE OF NEW JERSEY, AND THE CONGRESS AND EXECUTIVE BRANCHES OF THE UNITED STATES PROVIDE COVID-19 RELATED FINANCIAL SUPPORT TO NONPROFIT VETERAN AND COMMUNITY SERVICE ORGANIZATIONS

WHEREAS, the Borough of Bound Brook strongly supports and appreciates the charitable efforts of the nonprofit Veteran Organizations and the sacrifices made by all men and women of the armed forces – active duty, reserve and National Guard and

WHEREAS, the Borough of Bound Brook strongly supports and appreciates the Bound Brook nonprofit Service Clubs that provide charitable works for the community; and

WHEREAS, nonprofit Veteran Organizations and Community Service Organizations have been severely affected by the COVID-19 Pandemic with a reduction in administrative and social gathering opportunities and the inability to conduct fund raising events; and

WHEREAS, the twin crises of pandemic and recession are straining service organizations and could force as many as a third of them to dissolve, with donors facing financial problems and turning cautious because of political gridlock; and

WHEREAS, Somerset County, the State of New Jersey and the Congress and Executive Branches of the United States have not prioritized needed financial assistance to these organizations during this Pandemic crisis.

NOW, THEREFORE BE IT RESOLVED, that the Borough of Bound Brook formally requests that Somerset County, the State of New Jersey, the Congress, and the Executive Branch of the United States work to promote the charitable activities of service organizations and provide COVID-19 related financial assistance to nonprofit Veteran and Community Service Organizations including the American Legion, Veterans of Foreign Wars, Moose, Elks and Rotary Clubs.

| | Approved: |
|----------------------------------|-----------------------|
| Attest: | Mayor Robert P. Fazen |
| Jasmine D. Mathis, Borough Clerk | |

Date of Adoption: February 23, 2021

RESOLUTION 2021-037

RESOLUTION AUTHORIZING AN AGREEMENT WITH MIDDLSEX COUNTY FOR THE USE OF A SHARED RADIO NETWORK

WHEREAS, Middlesex County has constructed a NEW p25 Phase II, 700/800 megahertz, radio network with microwave redundancy for the purpose of improving public safety and public service communications and interoperability; and

WHEREAS, the Borough of Bound Brook ("the Borough") desires the ability to use the MCRN for purposes that have been approved by the MCRN Administrator; and

WHEREAS, Middlesex County and the Borough are authorized to enter into this Agreement, pursuant to Uniform Shared Services and Consolidation Act, N.J.S.A. 40A:65-1 et. seq. and N.J.S.A. 40A:11-5(2); and

WHEREAS, nothing in this Agreement is intended to reduce the Borough's authority over responsibility for events occurring within its jurisdiction.

NOW, THEREFORE, BE IT RESOLVED by the Borough Council of the Borough of Bound Brook, County of Somerset, State of New Jersey that the agreement is hereby approved and the Mayor is authorized to execute the agreement.

| | Approved: |
|----------------------------------|-----------------------|
| Attest: | Mayor Robert P. Fazen |
| Jasmine D. Mathis, Borough Clerk | |

Date of Adoption: February 23, 2021

RESOLUTION 2021-038

AUTHORIZING PRELIMINARY EXPENSES TO CONDUCT PROFESSIONAL SURVEYING SERVICES OF HAMILTON STREET AND VAN HORNE PLAZA AND AUTHORIZING A PAYMENT NOT TO EXCEED \$10,000

WHEREAS, the Borough Council of the Borough of Bound Brook, Somerset County hereby acknowledges the requirement of preliminary costs to determine the scope and cost of a proposed undertaking. The purpose of these preliminary costs is for Professional Surveying Services of Hamilton Street and Van Horne Plaza and the amount to be charged is for the purpose for which bonds may be issued under Chapter 2 of Title 40A;

NOW, THEREFORE, BE IT RESOLVED that the amount appropriated for Preliminary costs shall not exceed \$10,000 and the Chief Financial Officer has certified and is authorized to set up a "Reserve for Preliminary Expenses out of the Capital Improvement Fund of the General Capital Fund – Account No. 301400.

| | Approved: | |
|----------------------------------|-----------------------|--|
| Attest: | Mayor Robert P. Fazen | |
| Jasmine D. Mathis, Borough Clerk | | |

Date of Adoption: February 23, 2021

RESOLUTION 2021-039

RESOLUTION AUTHORIZING THE REFUND OF TAX OVERPAYMENTS PURSUANT TO NEW JERSEY STATE TAX COURT JUDGEMENTS 11887-2018, 011129-2019 and 012268-2020 for 423-425 EAST MAIN STREET, BLOCK 12, LOT 4 IN THE AMOUNT OF \$4,321.25

WHEREAS, the New Jersey State Tax Court ruled the property owner of 423-425 East Main Street overpaid taxes in 2018, 2019 and 2020; and

WHEREAS, the records of the Tax Collector reflect tax over payment as the following:

2018 \$1,233.34 2019 \$1,165.13 2020 \$1,922.78

Date of Adoption: February 23, 2021

NOW, THEREFORE, BE IT RESOLVED by the Mayor and Borough Council of the Borough of Bound Brook, County of Somerset, State of New Jersey that the Tax Collector is hereby authorized and directed to refund a total of \$4,321.25 to Waters, McPherson, McNeill, P.C. Attorneys at Law on behalf of Mazaraki, Inc. for the overpayment of 2018, 2019 and 2020 taxes as a result of New Jersey State Tax Court judgements 11887-2018, 011129-2019 and 012268-2020.

| | Approved: | |
|----------------------------------|-----------------------|--|
| Attest: | Mayor Robert P. Fazen | |
| Jasmine D. Mathis, Borough Clerk | | |

RESOLUTION 2021-040

NOTIFICATION OF APPLICATIONS FOR THE 2021 SOMERSET COUNTY COMMUNITY DEVELOPMENT BLOCK GRANT BY THE FOLLOWING NONPROFITS WITH INTENDED PROJECTS WITHIN THE BOROUGH OF BOUND BROOK

WHEREAS, the following non-profit groups located or implementing projects in the Borough of Bound Brook desire to participate in the 2021 Somerset County Community Development Block Grant Program:

WHEREAS, the Borough of Bound Brook governing body has been made aware of the intended projects from the each of the following non-profit groups;

Middle Earth

Date of Adoption: February 23, 2021

NOW, THEREFORE BE IT RESOLVED, by the Borough of Bound Brook Council that the Mayor and Clerk are also authorized to execute the applications from the non-profit groups listed above indicating that the Borough has been made aware of these applications.

| | Approved: |
|----------------------------------|-----------------------|
| Attest: | Mayor Robert P. Fazen |
| Jasmine D. Mathis, Borough Clerk | |

BOROUGH OF BOUND BROOK RESOLUTION 2021-041

APPROVAL OF VOUCHERS

BE IT HEREBY RESOLVED by the Mayor and Council of the Borough of Bound Brook, County of Somerset, and State of New Jersey that vouchers are approved for the following funds in the amount of \$2,673,396.44

| <u>FUND</u> | <u>AMOUNT</u> |
|--|-----------------------|
| CURRENT | \$ 2,499,677.96 |
| GRANT FUND | \$ 6, 240.00 |
| GENERAL CAPITAL | \$ 71,057.04 |
| GENERAL TRUST | \$43,965.00 |
| DOG/CAT TRUST | \$285.00 |
| RECREATION TRUST | \$ 9,700.00 |
| HOUSING REHAB | \$ 426.80 |
| UNEMPLOYMENT TRUST FUND | \$ 5,073.80 |
| TAX COLLECTOR TRUST | \$4,600.00 |
| TAX TITLE LIEN REDEMPTION | \$18,909.51 |
| DEVELOPERS ESCROW | \$10,168.25 |
| ENGINEERING ESCROW | \$3,293.08 |
| TOTAL | \$ 2,673,396.44 |
| Attest: | Approved: |
| Jasmine D. Mathis, Borough Clerk Date of Adoption: February 23, 2021 | Mayor Robert P. Fazen |

RESOLUTION 2021-042

RESOLUTION AUTHORIZING EXECUTIVE SESSION

WHEREAS, NJSA 10:4-12 allows for a public body to go into closed session during a public meeting; and

WHEREAS, the Borough of Bound Brook has deemed it necessary to go into closed session to discuss matters which are exempted from the public; and

WHEREAS, the regular meeting of the Borough of Bound Brook will reconvene.

NOW THEREFORE BE IT RESOLVED, that the Borough Council will go into closed session for the following reasons as outlined in NJSA 10:4-12; and

NOW THEREFORE BE IT FURTHER RESOLVED that the Borough of Bound Brook hereby declares that the discussion of subject(s) may be made public at a time when the Borough Attorney advises the Borough Council that the disclosure of the discussion will not detrimentally affect any right, interest or duty of the Borough or any other entity with respect to said discussion. That time is currently estimated as the time of said matter.

NOW THEREFORE BE IT FINALLY RESOLVED that the Borough is excluded from the portion of the meeting during which the discussion(s) shall take place and hereby directs the Municipal Clerk to take the appropriate action to effectuate the terms of this resolution.

Reason for Closed Session -

Date of Adoption: February 23, 2021

Any pending or anticipated litigation or contract negotiations which the public body is or may become a party. Any matters falling within the attorney-client privilege, to the extent that confidentiality is required in order for the attorney to exercise his ethical duties as lawyer. Under certain circumstances, if public disclosure of the matter would have a potentially negative impact on the borough's position in the litigation or negotiation, this information may be withheld until such time that the matter is concluded or the circumstances no longer present a potential impact.

| | Approved: | |
|----------------------------------|-----------------------|--|
| Attest: | Mayor Robert P. Fazen | |
| Jasmine D. Mathis, Borough Clerk | | |